

Instruction / Installation Sheet

1 & 2-Gang Low Voltage Mounting Brackets

- This product is designed for use with low voltage cables **ONLY**.
- **DO NOT** run or pull a TV cord or other electrical cords inside the wall.
- It is a violation of the National Electric Code (NEC) to run power cords or extension cords behind the wall.

Tools Needed

Pencil
Drywall Saw or Utility Knife
Philips Head Screw Driver

Installation

- Hold the low voltage mounting bracket with the face against the wall in your desired location.
- Use pencil and trace the two flat sides of the bracket (see fig. 1)
- Rotate the bracket 180°, aligning start and end points from your first mark and repeat previous step (see fig. 2)
- Cut along the traced line with a drywall saw or utility knife.
- Insert low voltage mounting bracket into opening. Tighten down each of the screws. As the wings tighten they will catch the back of the drywall, securing the plate in place.
- Install any standard low voltage single or dual gang wall plate to the bracket.



*1-Gang Model Shown

Caution:

- Never install low voltage wiring during lightning storms.
- Never touch un-insulated wires or terminals unless the wire has been disconnected at its network interface.
- Use caution when installing or modifying data or telecommunication lines.
- **DO NOT** alter, change, or disconnect existing telecommunication wires if you are unsure of their purpose or function.
- It is **NOT** recommended to install this product in close proximity to an electrical service panel to prevent interference from electrical current.

Important Instructions:

- Read and understand all instructions.
- Do not use this product near water, for example near bath tub, wash bowl, kitchen, sink, or laundry tub, in a wet basement, or near a swimming pool.
- **SAVE THESE INSTRUCTIONS.**